OTOMATIC

PRODUCT CARD

DPF 3Powers

LOW-FOAMING ACID CLEANER

22 L | PRO



INTENDED USE

Low-foaming acidic fluid for machine cleaning of **DPF filters** and **SCR catalysts**. Follow the cleaning machine instructions.

COMPOSITION

Citric acid monohydrate: 5-15%
Sulfamic acid: 5-15%

STORAGE

Store in the original container at **5-30°C**. Protect from freezing and direct sunlight.

DILUTION	TEMPERATURE	CLEANING TIME
0.5-2%	40-80°C	30-60 min

SAFETY & FIRST AID



H314: Causes severe skin burns and eye damage.

P260 Do not breathe mist, vapour or spray. **P280** Wear protective gloves, clothing, eye and face protection.

IN CASE OF EXPOSURE

IF SWALLOWED (P301+P330+P331)
Rinse mouth. Do NOT induce vomiting.

IF ON SKIN OR HAIR (P303+P361+P353)
Remove all contaminated clothing immediately. Rinse skin with water or shower.

IF INHALED (P304+P340)
Move to fresh air and keep comfortable for breathing.

ADDITIONAL PRECAUTIONS

IF IN EYES (P305+P351+P338)
Rinse cautiously with water for several minutes. Remove contact lenses if easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

P501 Dispose of contents and container at a hazardous/special waste collection point in accordance with applicable regulations.

TRANSPORT: UN 3265 - Corrosive liquid, acidic, organic, N.O.S. (citric acid, sulfamic acid), Class 8, PG III.

FOR PROFESSIONAL USE • USE ACCORDING TO MACHINE INSTRUCTIONS

OTOMATIC Smolec i Wronka sp. jawna
ul. Krakowska 83c, 34-120 Andrychów, Poland

+48 728 411 962
www.otomatic.eu